

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025561 A1

(51) International Patent Classification⁷: **G06T 5/00 //**
G02B 6/16, 6/34, G01N 33:52)

(21) International Application Number:
PCT/US2003/028887

(22) International Filing Date:
12 September 2003 (12.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/410,541 12 September 2002 (12.09.2002) US
10/645,689 20 August 2003 (20.08.2003) US
10/645,686 20 August 2003 (20.08.2003) US

(71) Applicant: **CIDRA CORPORATION** [US/US]; 50
Barnes Park North, Wallingford, CT 06492 (US).

(72) Inventors: **MOON, John**; 17 Promontory Drive, Walling-
ford, CT 06492 (US). **PUTNAM, Martin, A.**; 78 Lancaster
Way, Cheshire, CT 06410 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: CHEMICAL SYNTHESIS USING DIFFRACTION GRATING-BASED ENCODED OPTICAL ELEMENTS



(57) Abstract: An optical identification element and a microparticle comprising it, as well as a method of synthesizing a chemical on an optical element. The microbeads (8) have a plurality of unique identification digital codes based on a diffraction grating (12) disposed therein that are detected when illuminated by incident light (24). The incident light (24) may be directed transversely onto the side or onto an end of the tube (14) with a narrow band (single wavelength) or multiple wavelength source, in which case the code is represented by a spatial distribution of light or a wavelength spectrum, respectively. The assay stick (7) may be reused or disposed upon completion of the assay.



WO 2004/025561 A1

**Chemical Synthesis Using
Diffraction Grating-Based Encoded Optical Elements**

5 Cross References to Related Applications

 This application claims the benefit of US Provisional Patent Applications, Serial No. 60/410,541 (CiDRA Docket No. CC-543), filed Sept. 12, 2002, and is a continuation-in-part of US Patent Applications, Serial No. (CiDRA Docket No. CC-0648), filed Aug. 20, 2003, and is a continuation-in-part of US Patent Application,
10 Serial No. (CiDRA Docket No. CC-0649), filed Aug. 20, 2003, each of which are incorporated herein by reference in their entirety.

 US Patent Application Serial No. (CiDRA Docket No. CC-0648A) and Application Serial No. (CiDRA Docket No. CC-0650), filed contemporaneously
15 herewith, contains subject matter related to that disclosed herein, which is incorporated by reference in its entirety.

Technical Field

 This invention relates to chemical synthesis, and more particularly to chemical
20 synthesis that use optically encoded beads, micro-particles, or elements.

Background Art

 A common form of chemical synthesis in combinatorial chemistry is known as “solid phase” chemical synthesis. This synthesis technique uses encoded beads or
25 particles as a solid support for the synthesis of chemicals and or chemical libraries

 Existing technologies, such as bar codes, electronic microchips/transponders, radio-frequency identification (RFID), and fluorescence and other optical techniques, are often inadequate. For example, existing technologies may be too large for certain applications, may not provide enough different codes (i.e., limited multiplexing

capability), or cannot withstand harsh temperature, chemical, nuclear and/or electromagnetic environments, or may otherwise be not well suited for certain types of chemical synthesis or true combinatorial chemistry.

5 Therefore, it would be desirable to obtain a coding element or platform that provides the capability of providing many codes (e.g., greater than 1 million codes), that can be made very small, that can withstand harsh environments, and/or can enable "true" combinatorial chemistry.

Summary of the Invention

10 Objects of the present invention include provision of an optical identification element or platform that allows for a large number of distinct codes, can be made very small, and/or can withstand harsh environments.

15 According to the present invention, an optical identification element attached to a chemical, comprises an optical substrate; at least a portion of the substrate having at least one diffraction grating disposed therein, the grating having at least one refractive index pitch superimposed at a common location; the grating providing an output optical signal when illuminated by an incident light signal; the optical output signal being indicative of a code in the substrate; and the chemical being attached to the substrate.

20 The present invention provides an encoded optical element platform for performing large numbers of combinatorial chemistry tasks/experiments.

25 Also, the elements may be very small "microbeads" (or microelements or microparticles or encoded particles) for synthesis that requires small substrates (about 1-1000 microns), or larger "macroelements" for synthesis that allows for larger substrates or beads (e.g., 1-1000mm or much larger). The elements may also be referred to as encoded particles or encoded threads. Also, the element may be embedded within or part of a larger substrate or object. A common synthesis use will be as microbeads. Also, chemicals can be synthesized on microbeads located in a glass column reaction vessel.

The beads may be chemically coated before or after synthesis, to either enhance chemical synthesis or help preserve it after synthesis is complete.

The invention may be used with any known combinatorial chemistry or biochemistry synthesis process, and are especially adaptable to synthesis processes having solid phase immobilization. The invention may be used in many areas such as drug discovery, biology, proteomics, combinatorial chemistry, assays or multiplexed experiments. Any type of chemical, or molecule chain that can be synthesized on a glass or other solid support bead may be synthesized using the present invention as the solid support. For example, genes, DNA, cDNA, RNA, proteins, particles, biological particles, cells, molecules, atoms, nucleotides, oligomers, peptides, antigen, antibodies, ligands, receptors, hydrocarbons, polymers, radioactive or non-radioactive particles.

The elements also allow for quality control of the synthesized chemical to be easily tested, providing a higher level of quality chemicals.

The foregoing and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of exemplary embodiments thereof.

Brief Description of the Drawings

Fig. 1 is a side view of an optical identification element, in accordance with the present invention.

Fig. 2 is a top level optical schematic for reading a code in an optical identification element, in accordance with the present invention.

Fig. 3 is a flow chart for a chemical split and pool chemical synthesis process, in accordance with the present invention.

Fig. 4 is a diagram of a chemical split and pool synthesis apparatus, in accordance with the present invention.

Fig. 5 is an optical schematic for reading a code in an optical identification element, in accordance with the present invention.

Fig. 6 is an image of a code on a CCD camera from an optical identification element, in accordance with the present invention.

Fig. 7 is a graph showing an digital representation of bits in a code in an optical identification element, in accordance with the present invention.

5 Fig. 8 illustrations (a)-(c) show images of digital codes on a CCD camera, in accordance with the present invention.

Fig. 9 illustrations (a)-(d) show graphs of different refractive index pitches and a summation graph, in accordance with the present invention.

10 Fig. 10 is an alternative optical schematic for reading a code in an optical identification element, in accordance with the present invention.

Fig. 11 illustrations (a)-(b) are graphs of reflection and transmission wavelength spectrum for an optical identification element, in accordance with the present invention.

15 Figs. 12-13 are side views of a thin grating for an optical identification element, in accordance with the present invention.

Fig. 14 is a perspective view showing azimuthal multiplexing of a thin grating for an optical identification element, in accordance with the present invention.

Fig. 15 is side view of a blazed grating for an optical identification element, in accordance with the present invention.

20 Fig. 16 is a graph of a plurality of states for each bit in a code for an optical identification element, in accordance with the present invention.

Fig. 17 is a side view of an optical identification element where light is incident on an end face, in accordance with the present invention.

25 Figs. 18-19 are side views of an optical identification element where light is incident on an end face, in accordance with the present invention.

Figs. 20, illustrations (a)-(c) are side views of an optical identification element having a blazed grating, in accordance with the present invention.

Fig. 21 is a side view of an optical identification element having a coating, in accordance with the present invention.

Fig. 22 is a side view of whole and partitioned optical identification element, in accordance with the present invention.

Fig. 23 is a side view of an optical identification element having a grating across an entire dimension, in accordance with the present invention.

5 Fig. 24, illustrations (a)-(c), are perspective views of alternative embodiments for an optical identification element, in accordance with the present invention.

Fig. 25, illustrations (a)-(b), are perspective views of an optical identification element having multiple grating locations, in accordance with the present invention.

10 Fig. 26, is a perspective view of an alternative embodiment for an optical identification element, in accordance with the present invention.

Fig. 27 is a view an optical identification element having a plurality of gratings located rotationally around the optical identification element, in accordance with the present invention.

15 Fig. 28 illustrations (a)-(e) show various geometries of an optical identification element that may have holes therein, in accordance with the present invention.

Fig. 29 illustrations (a)-(c) show various geometries of an optical identification element that may have teeth thereon, in accordance with the present invention.

20 Fig. 30 illustrations (a)-(c) show various geometries of an optical identification element, in accordance with the present invention.

Fig. 31 is a side view an optical identification element having a reflective coating thereon, in accordance with the present invention.

25 Fig. 32 illustrations (a)-(b) are side views of an optical identification element polarized along an electric or magnetic field, in accordance with the present invention.

Best Mode for Carrying Out the Invention

Referring to Fig. 1, a diffraction grating-based optical identification element 8 (or encoded element or coded element) comprises a known optical substrate 10,

having an optical diffraction grating 12 disposed (or written, impressed, embedded, imprinted, etched, grown, deposited or otherwise formed) in the volume of or on a surface of a substrate 10. The grating 12 is a periodic or aperiodic variation in the effective refractive index and/or effective optical absorption of at least a portion of the substrate 10.

The optical identification element 8 described herein is the same as that described in Copending Patent Application Serial No. (CiDRA Docket No. CC-0648A), and in Copending Patent Application Serial No. (CiDRA Docket No. CC-0649A), both filed contemporaneously herewith, which are both incorporated herein by reference in their entirety.

In particular, the substrate 10 has an inner region 20 where the grating 12 is located. The inner region 20 may be photosensitive to allow the writing or impressing of the grating 12. The substrate 10 has an outer region 18, which does not have the grating 12 therein.

The grating 12 is a combination of one or more individual spatial periodic sinusoidal variations (or components) in the refractive index that are collocated at substantially the same location on the substrate 10 along the length of the grating region 20, each having a spatial period (or pitch) Λ . The resultant combination of these individual pitches is the grating 12, comprising spatial periods (Λ_1 - Λ_n) each representing a bit in the code. Thus, the grating 12 represents a unique optically readable code, made up of bits, where a bit corresponds to a unique pitch Λ within the grating 12. Accordingly, for a digital binary (0-1) code, the code is determined by which spatial periods (Λ_1 - Λ_n) exist (or do not exist) in a given composite grating 12. The code or bits may also be determined by additional parameters (or additional degrees of multiplexing), and other numerical bases for the code may be used, as discussed herein and/or in the aforementioned patent application.

The grating 12 may also be referred to herein as a composite or collocated grating. Also, the grating 12 may be referred to as a "hologram", as the grating 12

transforms, translates, or filters an input optical signal to a predetermined desired optical output pattern or signal.

5 The substrate 10 has an outer diameter D1 and comprises silica glass (SiO_2) having the appropriate chemical composition to allow the grating 12 to be disposed therein or thereon. Other materials for the optical substrate 10 may be used if desired. For example, the substrate 10 may be made of any glass, e.g., silica, phosphate glass, borosilicate glass, or other glasses, or made of glass and plastic, or solely plastic. For high temperature or harsh chemical applications, the optical substrate 10 made of a glass material is desirable. If a flexible substrate is needed, plastic, rubber or
10 polymer-based substrate may be used. The optical substrate 10 may be any material capable of having the grating 12 disposed in the grating region 20 and that allows light to pass through it to allow the code to be optically read.

The optical substrate 10 with the grating 12 has a length L and an outer diameter D1, and the inner region 20 diameter D. The length L can range from very
15 small "microbeads" (or microelements, micro-particles, or encoded particles), about 1-1000 microns or smaller, to larger "macrobeads" or "macroelements" for larger applications (about 1.0 - 1000 mm or greater). In addition, the outer dimension D1 can range from small (less than 1000 microns) to large (1.0 - 1000 mm and greater). Other dimensions and lengths for the substrate 10 and the grating 12 may be used.

20 The grating 12 may have a length L_g of about the length L of the substrate 10. Alternatively, the length L_g of the grating 12 may be shorter than the total length L of the substrate 10.

The outer region 18 is made of pure silica (SiO_2) and has a refractive index n_2 of about 1.458 (at a wavelength of about 1553 nm), and the inner grating region 20 of
25 the substrate 10 has dopants, such as germanium and/or boron, to provide a refractive index n_1 of about 1.453, which is less than that of outer region 18 by about 0.005. Other indices of refraction n_1, n_2 for the grating region 20 and the outer region 18, respectively, may be used, if desired, provided the grating 12 can be impressed in the desired grating region 20. For example, the grating region 20 may have an index of

refraction that is larger than that of the outer region 18 or grating region 20 may have the same index of refraction as the outer region 18 if desired.

Referring to Fig. 2, an incident light 24 of a wavelength λ , e.g., 532 nm from a known frequency doubled Nd:YAG laser or 632nm from a known Helium-Neon laser, is incident on the grating 12 in the substrate 10. Any other input wavelength λ can be used if desired provided λ is within the optical transmission range of the substrate (discussed more herein and/or in the aforementioned patent application). A portion of the input light 24 passes straight through the grating 12, as indicated by a line 25. The remainder of the input light 24 is reflected by the grating 12, as indicated by a line 27 and provided to a detector 29. The output light 27 may be a plurality of beams, each having the same wavelength λ as the input wavelength λ and each having a different output angle indicative of the pitches (Λ_1 - Λ_n) existing in the grating 12.

Alternatively, the input light 24 may be a plurality of wavelengths and the output light 27 may have a plurality of wavelengths indicative of the pitches (Λ_1 - Λ_n) existing in the grating 12. Alternatively, the output light may be a combination of wavelengths and output angles. The above techniques are discussed in more detail herein and/or in the aforementioned patent application.

The detector 29 has the necessary optics, electronics, software and/or firmware to perform the functions described herein. In particular, the detector reads the optical signal 27 diffracted or reflected from the grating 12 and determines the code based on the pitches present or the optical pattern, as discussed more herein or in the aforementioned patent application. An output signal indicative of the code is provided on a line 31.

Referring to Fig. 3, the optical elements described herein may be used to synthesize chemicals in a known split and pool synthesis technique. In particular, a known split and pool bead based synthesis process 801, may be performed starting with a step 800 where a predetermined number M of compounds or chemicals are provided each in a separate bin or container and at step 802 where a predetermined number X of microbeads 8 are provided each having its own unique code. Steps 800,

802 are material preparation steps and can be done in either order. After the materials are prepared, a step 803 combines or pools all the beads together. Then, a step 804 determines the code for each microbead 8. This step can be skipped on the first time through the process if it is desired to randomly split up the beads into groups, i.e., to not split the groups up by code on bead during the first run. Next a step 806 sorts the beads based on its code and deposits the bead into the appropriate bin for the chemical to be added to the bead.

Next, a step 808 tests to see if the chemical synthesis is complete for each bead. If not the process goes back to step 803 where the remaining beads are recombines or re-pools and the process starts again. The loop 814 repeats a predetermined number of times N, where each time through the loop 814 another chemical is added to each of the beads. If certain beads are to have fewer chemicals than others, then certain beads will drop out of the process before others. When the step 808 concludes that one or more beads have completed their synthesis process, a step 812 logs the completion of that bead and the remainder of the beads continue until all desired chemicals have synthesized on the beads.

For example, for $M=4$ compounds and $N=10$ chemicals to add to each bead, the total number of different codes needed would be 1,048,576 or M^N and if there will be only one bead with each desired chemical (i.e., no redundancy), then the number of beads X would also be $M^N = 1,048,576$.

Referring to Fig. 4, an automated synthesis machine is shown for synthesizing a chemical having four different possible compounds or cells or molecules (e.g., GCAT for a DNA synthesis), where a main bin 830 receives or pools all the beads 8 and provides the beads 8 to a sorting machine 832, which performs the sorting step 806 in the loop 814. In addition the machine 832 deposits the beads in the proper bins 834, 836, 838, 840, having the bases G, C, A, T, respectively. Any other four chemicals can be used if desired. Once the specific base has been attached to a bead it is dropped or placed in a device which transports the beads back into the main bin 830 for

resorting by the machine 832. When synthesis has been completed on a given bead the machine deposits the completed bead in a done bin 844.

If it is desired to produce multiple of the same chemical on separate beads this can be done by having multiple beads with the same code, or presetting certain groups of codes to have the same chemical composition. In that case, each of these beads
5 may go to the same bins in the same order as a group.

The present invention may be used with any known combinatorial chemistry, chemical synthesis process, or synthesizing labeled combinatorial chemistry libraries, and are especially adaptable to solid phase synthesis, for example: US Patents,
10 6,417,010, "Methods and Apparatus for Synthesizing Labeled Combinatorial Chemistry Libraries", 6,558,904 entitled "Method for producing structured, self-organized molecular monolayers of individual molecular species, in particular substance libraries"; 6,541,276 entitled "Methods for solid-phase synthesis of hydroxylamine compounds and derivatives and combinatorial libraries thereof";

15 6,541,211 "Apparatus and method for synthesizing combinational libraries"; 6,528,324 entitled "Apparatus for pre-determined mass sorting of positional-encoded solid phase synthesis supports"; 6,506,558 entitled "Very large scale immobilized polymer synthesis"; 6,495,539 entitled "B-lactam-like chaperone inhibitors"; 6,468,740 entitled "Cyclic and substituted immobilized molecular synthesis";
20 6,417,010 entitled "Methods and apparatus for synthesizing labeled combinatorial chemistry libraries"; 6,410,643 entitled "Solid phase synthesis method and reagent"; 6,410,342 entitled "Method and apparatus for controlled photoelution"; 6,387,636 entitled "Method of shielding biosynthesis reactions from the ambient environment on an array"; 6,372,885 entitled "Solid-phase technology for the preparation of amides";
25 6,368,874 entitled "Methods for hard-tagging an encoded synthetic library"; 6,362,009 entitled "Solid phase synthesis of heterocycles"; 6,346,423 entitled "Methods and compositions for producing biopolymeric arrays"; 6,329,210 entitled "Method and apparatus for high volume polymer synthesis"; 6,294,694 entitled "Matrix metalloproteinase inhibitors and method of using same"; 6,274,385

entitled "Attached tags for use in combinatorial chemistry synthesis"; 6,265,228
entitled "Process for preparing combinatorial amide alcohol libraries"; 6,251,595
entitled "Methods and devices for carrying out chemical reactions"; 6,127,190
entitled "Method for producing combinatorial libraries having a predetermined
5 frequency of each species of test compound"; 5,929,208 entitled "Methods for
electronic synthesis of polymers"; 5,886,186 entitled "Synthesis of substituted N-
heteroaromatic compounds and methods of use thereof"; 5,885,837 entitled "Very
large scale immobilized polymer synthesis using mechanically directed flow paths";
5,859,191 entitled "Method for the site-specific modification of peptide alpha
10 amines"; 5,763,263 entitled "Method and apparatus for producing position
addressable combinatorial libraries"; 5,712,171 entitled "Method of generating a
plurality of chemical compounds in a spatially arranged array"; 5,690,894 entitled
"High density array fabrication and readout method for a fiber optic biosensor";
5,545,568 entitled "Solid phase and combinatorial synthesis of compounds on a solid
15 support"; 5,545,531 entitled "Methods for making a device for concurrently
processing multiple biological chip assays"; 5,539,083 entitled "Peptide nucleic acid
combinatorial libraries and improved methods of synthesis"; 5,384,261 entitled
"Very large scale immobilized polymer synthesis using mechanically directed flow
paths"; 5,288,514 entitled "Solid phase and combinatorial synthesis of
20 benzodiazepine compounds on a solid support"; 5,264,563 entitled "Process for
synthesizing oligonucleotides with random codons"; 5,010,175 entitled "General
method for producing and selecting peptides with specific properties"; 6,465,192
entitled "Compounds and methods for the inhibition of protein-protein interactions";
6,440,669 entitled "Methods for applying small volumes of reagents"; 6,406,844
25 entitled "Very large scale immobilized polymer synthesis"; 6,329,010 entitled
"Method and apparatus for high volume polymer synthesis"; 6,316,623 entitled
"Ethylenediamine compound libraries"; 5,780,241 entitled "Complex chemical
libraries"; 5,712,171 entitled "Method of generating a plurality of chemical
compounds in a spatially arranged array"; 5,593,853 entitled "Generation and

screening of synthetic drug libraries”; 6,569,631 entitled “Microplate thermal shift assay for ligand development using 5-(4”dimethylaminophenyl)- 2-(4’-phenyl)oxazole derivative fluorescent dyes”; 6,503,759 entitled “Complex combinatorial chemical libraries encoded with tags”; 6,492,125 entitled “Method to assess library X library interactions”; 6,457,807 entitled “Mass-based encoding and qualitative analysis of combinatorial libraries”; 6,455,263 entitled “Small molecule library screening using FACS”; 6,096,496 entitled “Supports incorporating vertical cavity emitting lasers and tracking apparatus for use in combinatorial synthesis”; 5,770,455 entitled “Methods and apparatus for synthesizing labeled combinatorial chemistry libraries”; 5,751,629 entitled “Remotely programmable matrices with memories”; 6,537,504 “Method and apparatus for concurrent and sequential multi-step reactions for producing a plurality of different chemical compounds”; 6,468,806 “Potential masking systems and methods for combinatorial library synthesis”; 6,429,027 “Composite arrays utilizing microspheres”; 6,420,169 “Apparatus for forming polynucleotides or polypeptides”; 6,448,443 “Synthesis of combinatorial libraries of compounds reminiscent of natural products”; 5,840,485 “Topologically segregated, encoded solid phase libraries”.

Referring to Fig. 5, The reflected light 27, comprises a plurality of beams 26-36 that pass through a lens 37, which provides focused light beams 46-56, respectively, which are imaged onto a CCD camera 60. The lens 37 and the camera 60, and any other necessary electronics or optics for performing the functions described herein, make up the reader 29. Instead of or in addition to the lens 37, other imaging optics may be used to provide the desired characteristics of the optical image/signal onto the camera 60 (e.g., spots, lines, circles, ovals, etc.), depending on the shape of the substrate 10 and input optical signals. Also, instead of a CCD camera other devices may be used to read/capture the output light.

Referring to Fig. 6, the image on the CCD camera 60 is a series of illuminated stripes indicating ones and zeros of a digital pattern or code of the grating 12 in the

element 8. Referring to Fig. 7, lines 68 on a graph 70 are indicative of a digitized version of the image of Fig. 6 as indicated in spatial periods (Λ_1 - Λ_n).

Each of the individual spatial periods (Λ_1 - Λ_n) in the grating 12 is slightly different, thus producing an array of N unique diffraction conditions (or diffraction angles) discussed more hereinafter. When the element 8 is illuminated from the side, in the region of the grating 12, at an appropriate input angle, e.g., about 30 degrees, with a single input wavelength λ (monochromatic) source, the diffracted (or reflected) beams 26-36 are generated. Other input angles θ_i may be used if desired, depending on various design parameters as discussed herein and/or in the aforementioned patent application, and provided that a known diffraction equation (Eq. 1 below) is satisfied:

$$\sin(\theta_i) + \sin(\theta_o) = m\lambda / n\Lambda \quad \text{Eq. 1}$$

where Eq. 1 is diffraction (or reflection or scatter) relationship between input wavelength λ , input incident angle θ_i , output incident angle θ_o , and the spatial period Λ of the grating 12. Further, m is the "order" of the reflection being observed, and n is the refractive index of the substrate 10. The value of $m=1$ or first order reflection is acceptable for illustrative purposes. Eq. 1 applies to light incident on outer surfaces of the substrate 10 which are parallel to the longitudinal axis of the grating (or the k_B vector). Because the angles θ_i, θ_o are defined outside the substrate 10 and because the effective refractive index of the substrate 10 is substantially a common value, the value of n in Eq. 1 cancels out of this equation.

Thus, for a given input wavelength λ , grating spacing Λ , and incident angle of the input light θ_i , the angle θ_o of the reflected output light may be determined.

Solving Eq. 1 for θ_o and plugging in $m=1$, gives:

$$\theta_o = \sin^{-1}(\lambda/\Lambda - \sin(\theta_i)) \quad \text{Eq. 2}$$

For example, for an input wavelength $\lambda = 532$ nm, a grating spacing $\Lambda = 0.532$ microns (or 532 nm), and an input angle of incidence $\theta_i = 30$ degrees, the output angle of reflection will be $\theta_o = 30$ degrees. Alternatively, for an input wavelength $\lambda = 632$ nm, a grating spacing $\Lambda = 0.532$ microns (or 532 nm), and an input angle θ_i of 30

degrees, the output angle of reflection θ_o will be at 43.47 degrees, or for an input angle $\theta_i = 37$ degrees, the output angle of reflection will be $\theta_o = 37$ degrees. Any input angle that satisfies the design requirements discussed herein and/or in the aforementioned patent application may be used.

5 In addition, to have sufficient optical output power and signal to noise ratio, the output light 27 should fall within an acceptable portion of the Bragg envelope (or normalized reflection efficiency envelope) curve 200, as indicated by points 204, 206, also defined as a Bragg envelope angle θ_B , as also discussed herein and/or in the aforementioned patent application. The curve 200 may be defined as:

$$10 \quad I(k_i, k_o) \approx [KD]^2 \operatorname{sinc}^2 \left[\frac{(k_i - k_o)D}{2} \right] \quad \text{Eq. 3}$$

where $K = 2\pi\delta n/\lambda$, where, δn is the local refractive index modulation amplitude of the grating and λ is the input wavelength, $\operatorname{sinc}(x) = \sin(x)/x$, and the vectors $k_i = 2\pi\cos(\theta_i)/\lambda$ and $k_o = 2\pi\cos(\theta_o)/\lambda$ are the projections of the incident light and the output (or reflected) light, respectively, onto the line 203 normal to the axial direction of the grating 12 (or the grating vector k_B), D is the thickness or depth of the grating 12 as measured along the line 203 (normal to the axial direction of the grating 12). Other substrate shapes than a cylinder may be used and will exhibit a similar peaked characteristic of the Bragg envelope. We have found that a value for δn of about 10^{-4} in the grating region of the substrate is acceptable; however, other values may be used if desired.

20 Rewriting Eq. 3 gives the reflection efficiency profile of the Bragg envelope as:

$$I(k_i, k_o) \approx \left[\frac{2\pi \cdot \delta n \cdot D}{\lambda} \right]^2 \left[\frac{\sin(x)}{x} \right]^2 \quad \text{Eq. 4}$$

where: $x = (k_i - k_o)D/2 = (\pi D/\lambda) * (\cos \theta_i - \cos \theta_o)$

25 Thus, when the input angle θ_i is equal to the output (or reflected) angle θ_o (i.e., $\theta_i = \theta_o$), the reflection efficiency I (Eqs. 3 & 4) is maximized, which is at the

center or peak of the Bragg envelope. When $\theta_i = \theta_o$, the input light angle is referred to as the Bragg angle as is known. The efficiency decreases for other input and output angles (i.e., $\theta_i \neq \theta_o$), as defined by Eqs. 3 & 4. Thus, for maximum reflection efficiency and thus output light power, for a given grating pitch Λ and input wavelength, the angle θ_i of the input light 24 should be set so that the angle θ_o of the reflected output light equals the input angle θ_i .

Also, as the thickness or diameter D of the grating decreases, the width of the $\sin(x)/x$ function (and thus the width of the Bragg envelope) increases and, the coefficient to or amplitude of the sinc^2 (or $(\sin(x)/x)^2$ function (and thus the efficiency level across the Bragg envelope) also increases, and vice versa. Further, as the wavelength λ increases, the half-width of the Bragg envelope as well as the efficiency level across the Bragg envelope both decrease. Thus, there is a trade-off between the brightness of an individual bit and the number of bits available under the Bragg envelope. Ideally, δn should be made as large as possible to maximize the brightness, which allows D to be made smaller.

From Eq. 3 and 4, the half-angle of the Bragg envelope θ_B is defined as:

$$\theta_B = \frac{\eta \lambda}{\pi D \sin(\theta_i)} \quad \text{Eq. 5}$$

where η is a reflection efficiency factor which is the value for x in the $\text{sinc}^2(x)$ function where the value of $\text{sinc}^2(x)$ has decreased to a predetermined value from the maximum amplitude as indicated by points 204,206 on the curve 200.

We have found that the reflection efficiency is acceptable when $\eta \leq 1.39$. This value for η corresponds to when the amplitude of the reflected beam (i.e., from the $\text{sinc}^2(x)$ function of Eqs. 3 & 4) has decayed to about 50% of its peak value. In particular, when $x = 1.39 = \eta$, $\text{sinc}^2(x) = 0.5$. However, other values for efficiency thresholds or factor in the Bragg envelope may be used if desired.

The beams 26-36 are imaged onto the CCD camera 60 to produce the pattern of light and dark regions 120-132 representing a digital (or binary) code, where light

= 1 and dark = 0 (or vice versa). The digital code may be generated by selectively creating individual index variations (or individual gratings) with the desired spatial periods Λ_1 - Λ_n . Other illumination, readout techniques, types of gratings, geometries, materials, etc. may be used as discussed in the aforementioned patent application.

Referring to Fig.8, illustrations (a)-(c), for the grating 12 in a cylindrical substrate 10 having a sample spectral 17 bit code (i.e., 17 different pitches Λ_1 - Λ_{17}), the corresponding image on the CCD (Charge Coupled Device) camera 60 is shown for a digital pattern of 7 bits turned on (10110010001001001); 9 bits turned on of (11000101010100111); all 17 bits turned on of (11111111111111111).

For the images in Fig. 8, the length of the substrate 10 was 450 microns, the outer diameter D_1 was 65 microns, the inner diameter D was 14 microns, δn for the grating 12 was about 10^{-4} , n_1 in portion 20 was about 1.458 (at a wavelength of about 1550 nm), n_2 in portion 18 was about 1.453, the average pitch spacing Λ for the grating 12 was about 0.542 microns, and the spacing between pitches $\Delta\Lambda$ was about 0.36 % of the adjacent pitches Λ .

Referring to Fig. 9, illustration (a), the pitch Λ of an individual grating is the axial spatial period of the sinusoidal variation in the refractive index n_1 in the region 20 of the substrate 10 along the axial length of the grating 12 as indicated by a curve 90 on a graph 91. Referring to Fig. 9, illustration (b), a sample composite grating 12 comprises three individual gratings that are co-located on the substrate 10, each individual grating having slightly different pitches, Λ_1 , Λ_2 , Λ_3 , respectively, and the difference (or spacing) $\Delta\Lambda$ between each pitch Λ being about 3.0 % of the period of an adjacent pitch Λ as indicated by a series of curves 92 on a graph 94. Referring to Fig. 9, illustration (c), three individual gratings, each having slightly different pitches, Λ_1 , Λ_2 , Λ_3 , respectively, are shown, the difference $\Delta\Lambda$ between each pitch Λ being about 0.3% of the pitch Λ of the adjacent pitch as shown by a series of curves 95 on a graph 97. The individual gratings in Fig. 9, illustrations (b) and (c) are shown to all start at 0 for illustration purposes; however, it should be understood that, the separate

gratings need not all start in phase with each other. Referring to Fig. 9, illustration (d), the overlapping of the individual sinusoidal refractive index variation pitches Λ_1 - Λ_n in the grating region 20 of the substrate 10, produces a combined resultant refractive index variation in the composite grating 12 shown as a curve 96 on a graph 98 representing the combination of the three pitches shown in Fig. 9, illustration (b). Accordingly, the resultant refractive index variation in the grating region 20 of the substrate 10 may not be sinusoidal and is a combination of the individual pitches Λ (or index variation).

The maximum number of resolvable bits N , which is equal to the number of different grating pitches Λ (and hence the number of codes), that can be accurately read (or resolved) using side-illumination and side-reading of the grating 12 in the substrate 10, is determined by numerous factors, including: the beam width w incident on the substrate (and the corresponding substrate length L and grating length L_g), the thickness or diameter D of the grating 12, the wavelength λ of incident light, the beam divergence angle θ_R , and the width of the Bragg envelope θ_B (discussed more in the aforementioned patent application), and may be determined by the equation:

$$N \cong \frac{\eta \beta L}{2 D \sin(\theta_i)} \quad \text{Eq. 6}$$

Referring to Fig. 10, instead of having the input light 24 at a single wavelength λ (monochromatic) and reading the bits by the angle θ_o of the output light, the bits (or grating pitches Λ) may be read/detected by providing a plurality of wavelengths and reading the wavelength spectrum of the reflected output light signal. In this case, there would be one bit per wavelength, and thus, the code is contained in the wavelength information of the reflected output signal.

In this case, each bit (or Λ) is defined by whether its corresponding wavelength falls within the Bragg envelope, not by its angular position within the Bragg envelope 200. As a result, it is not limited by the number of angles that can fit in the Bragg envelope 200 for a given composite grating 12, as in the embodiment discussed hereinbefore. Thus, using multiple wavelengths, the only limitation in the

number of bits N is the maximum number of grating pitches Λ that can be superimposed and optically distinguished in wavelength space for the output beam.

Referring to Figs. 10 and 11, illustration (a), the reflection wavelength spectrum (λ_1 - λ_n) of the reflected output beam 310 will exhibit a series of reflection peaks 695, each appearing at the same output Bragg angle θ_o . Each wavelength peak 695 (λ_1 - λ_n) corresponds to an associated spatial period (Λ_1 - Λ_n), which make up the grating 12.

One way to measure the bits in wavelength space is to have the input light angle θ_i equal to the output light angle θ_o , which is kept at a constant value, and to provide an input wavelength λ that satisfies the diffraction condition (Eq. 1) for each grating pitch Λ . This will maximize the optical power of the output signal for each pitch Λ detected in the grating 12.

Referring to 11, illustration (b), the transmission wavelength spectrum of the transmitted output beam 330 (which is transmitted straight through the grating 12) will exhibit a series of notches (or dark spots) 696. Alternatively, instead of detecting the reflected output light 310, the transmitted light 330 may be detected at the detector/reader 308. It should be understood that the optical signal levels for the reflection peaks 695 and transmission notches 696 will depend on the "strength" of the grating 12, i.e., the magnitude of the index variation n in the grating 12.

In Fig. 10, the bits may be detected by continuously scanning the input wavelength. A known optical source 300 provides the input light signal 24 of a coherent scanned wavelength input light shown as a graph 304. The source 300 provides a sync signal on a line 306 to a known reader 308. The sync signal may be a timed pulse or a voltage ramped signal, which is indicative of the wavelength being provided as the input light 24 to the substrate 10 at any given time. The reader 308 may be a photodiode, CCD camera, or other optical detection device that detects when an optical signal is present and provides an output signal on a line 309 indicative of the code in the substrate 10 or of the wavelengths present in the output light, which is directly related to the code, as discussed herein. The grating 12 reflects

the input light 24 and provides an output light signal 310 to the reader 308. The wavelength of the input signal is set such that the reflected output light 310 will be substantially in the center 314 of the Bragg envelope 200 for the individual grating pitch (or bit) being read.

5 Alternatively, the source 300 may provide a continuous broadband wavelength input signal such as that shown as a graph 316. In that case, the reflected output beam 310 signal is provided to a narrow band scanning filter 318 which scans across the desired range of wavelengths and provides a filtered output optical signal 320 to the reader 308. The filter 318 provides a sync signal on a line 322 to the reader, which is
10 indicative of which wavelengths are being provided on the output signal 320 to the reader and may be similar to the sync signal discussed hereinbefore on the line 306 from the source 300. In this case, the source 300 does not need to provide a sync signal because the input optical signal 24 is continuous. Alternatively, instead of having the scanning filter being located in the path of the output beam 310, the
15 scanning filter may be located in the path of the input beam 24 as indicated by the dashed box 324, which provides the sync signal on a line 323.

Alternatively, instead of the scanning filters 318,324, the reader 308 may be a known optical spectrometer (such as a known spectrum analyzer), capable of measuring the wavelength of the output light.

20 The desired values for the input wavelengths λ (or wavelength range) for the input signal 24 from the source 300 may be determined from the Bragg condition of Eq. 1, for a given grating spacing Λ and equal angles for the input light θ_i and the angle light θ_o . Solving Eq. 1 for λ and plugging in $m=1$, gives:

$$\lambda = \Lambda [\sin(\theta_o) + \sin(\theta_i)] \quad \text{Eq.}$$

25 7

It is also possible to combine the angular-based code detection with the wavelength-based code detection, both discussed hereinbefore. In this case, each readout wavelength is associated with a predetermined number of bits within the

Bragg envelope. Bits (or grating pitches Λ) written for different wavelengths do not show up unless the correct wavelength is used.

Accordingly, the bits (or grating pitches Λ) can be read using one wavelength and many angles, many wavelengths and one angle, or many wavelengths and many angles.

Referring to Fig. 12, the grating 12 may have a thickness or depth D which is comparable or smaller than the incident beam wavelength λ . This is known as a "thin" diffraction grating (or the full angle Bragg envelope is 180 degrees). In that case, the half-angle Bragg envelope θ_B is substantially 90 degrees; however, δn must be made large enough to provide sufficient reflection efficiency, per Eqs. 3 and 4. In particular, for a "thin" grating, $D \cdot \delta n \approx \lambda/2$, which corresponds to a π phase shift between adjacent minimum and maximum refractive index values of the grating 12.

It should be understood that there is still a trade-off discussed hereinbefore with beam divergence angle θ_R and the incident beam width (or length L of the substrate), but the accessible angular space is theoretically now 90 degrees. Also, for maximum efficiency, the phase shift between adjacent minimum and maximum refractive index values of the grating 12 should approach a π phase shift; however, other phase shifts may be used.

In this case, rather than having the input light 24 coming in at the conventional Bragg input angle θ_i , as discussed hereinbefore and indicated by a dashed line 701, the grating 12 is illuminated with the input light 24 oriented on a line 705 orthogonal to the longitudinal grating vector 705. The input beam 24 will split into two (or more) beams of equal amplitude, where the exit angle θ_o can be determined from Eq. 1 with the input angle $\theta_i=0$ (normal to the longitudinal axis of the grating 12).

In particular, from Eq. 1, for a given grating pitch Λ_1 , the $\pm 1^{\text{st}}$ order beams ($m=+1$ and $m=-1$), corresponds to output beams 700, 702, respectively. For the $\pm 2^{\text{nd}}$ order beams ($m=+2$ and $m=-2$), corresponds to output beams 704, 706, respectively. The 0^{th} order (undefracted) beam ($m=0$), corresponds to beam 708 and passes straight

through the substrate. The output beams 700-708 project spectral spots or peaks 710-718, respectively, along a common plane, shown from the side by a line 709, which is parallel to the upper surface of the substrate 10.

For example, for a grating pitch $\Lambda = 1.0 \text{ } \mu\text{m}$, and an input wavelength $\lambda = 400 \text{ nm}$, the exit angles θ_o are $\sim \pm 23.6$ degrees (for $m = \pm 1$), and ± 53.1 degrees (from $m = \pm 2$), from Eq. 1. It should be understood that for certain wavelengths, certain orders (e.g., $m = \pm 2$) may be reflected back toward the input side or otherwise not detectable at the output side of the grating 12.

Alternatively, one can use only the $\pm 1^{\text{st}}$ order ($m = \pm 1$) output beams for the code, in which case there would be only 2 peaks to detect, 712, 714. Alternatively, one can also use any one or more pairs from any order output beam that is capable of being detected. Alternatively, instead of using a pair of output peaks for a given order, an individual peak may be used.

Referring to Fig. 13, if two pitches Λ_1, Λ_2 exist in the grating 12, two sets of peaks will exist. In particular, for a second grating pitch Λ_2 , the $\pm 1^{\text{st}}$ order beams ($m=+1$ and $m=-1$), corresponds to output beams 720,722, respectively. For the $\pm 2^{\text{nd}}$ order beams ($m=+2$ and $m=-2$), corresponds to output beams 724,726, respectively. The 0^{th} order (un-defracted) beam ($m=0$), corresponds to beam 718 and passes straight through the substrate. The output beams 720-726 corresponding to the second pitch Λ_2 project spectral spots or peaks 730-736, respectively, which are at a different location than the point 710-716, but along the same common plane, shown from the side by the line 709.

Thus, for a given pitch Λ (or bit) in a grating, a set of spectral peaks will appear at a specific location in space. Thus, each different pitch corresponds to a different elevation or output angle which corresponds to a predetermined set of spectral peaks. Accordingly, the presence or absence of a particular peak or set of spectral peaks defines the code.

In general, if the angle of the grating 12 is not properly aligned with respect to the mechanical longitudinal axis of the substrate 10, the readout angles may no longer

be symmetric, leading to possible difficulties in readout. With a thin grating, the angular sensitivity to the alignment of the longitudinal axis of the substrate 10 to the input angle θ_i of incident radiation is reduced or eliminated. In particular, the input light can be oriented along substantially any angle θ_i with respect to the grating 12 without causing output signal degradation, due the large Bragg angle envelope. Also, if the incident beam 24 is normal to the substrate 10, the grating 12 can be oriented at any rotational (or azimuthal) angle without causing output signal degradation.

However, in each of these cases, changing the incident angle θ_i will affect the output angle θ_o of the reflected light in a predetermined predictable way, thereby allowing for accurate output code signal detection or compensation.

Referring to Fig. 14 , for a thin grating, in addition to multiplexing in the elevation or output angle based on grating pitch Λ , the bits can also be multiplexed in an azimuthal (or rotational) angle θ_a of the substrate. In particular, a plurality of gratings 750,752,754,756 each having the same pitch Λ are disposed in a surface 701 of the substrate 10 and located in the plane of the substrate surface 701. The input light 24 is incident on all the gratings 750,752,754,756 simultaneously. Each of the gratings provides output beams oriented based on the grating orientation. For example, the grating 750 provides the output beams 764,762, the grating 752 provides the output beams 766,768, the grating 754 provides the output beams 770,772, and the grating 756 provides the output beams 774,776. Each of the output beams provides spectral peaks or spots (similar to that discussed hereinbefore), which are located in a plane 760 that is parallel to the substrate surface plane 701. In this case, a single grating pitch Λ can produce many bits depending on the number of gratings that can be placed at different azimuthal (rotational) angles on the surface of the substrate 10 and the number of output beam spectral peaks that can be spatially and optically resolved/detected. Each bit may be viewed as the presence or absence of a pair of peaks located at a predetermined location in space in the plane 760. Note that this example uses only the $m = \pm 1^{\text{st}}$ order for each reflected output beam. Alternatively, the detection may also use the $m = \pm 2^{\text{nd}}$ order. In that case, there would be two

additional output beams and peaks (not shown) for each grating (as discussed hereinbefore) that may lie in the same plane as the plane 760 and may be on a concentric circle outside the circle 760.

5 In addition, the azimuthal multiplexing can be combined with the elevation or output angle multiplexing discussed hereinbefore to provide two levels of multiplexing. Accordingly, for a thin grating, the number of bits can be multiplexed based on the number of grating pitches Λ and/or geometrically by the orientation of the grating pitches.

10 Furthermore, if the input light angle θ_i is normal to the substrate 10, the edges of the substrate 10 no longer scatter light from the incident angle i_n into the "code angular space", as discussed herein and/or in the aforementioned patent application.

Also, in the thin grating geometry, a continuous broadband wavelength source may be used as the optical source if desired.

15 Referring to Fig. 15, instead of or in addition to the pitches Λ in the grating 12 being oriented normal to the longitudinal axis, the pitches may be created at an angle θ_g . In that case, when the input light 24 is incident normal to the surface 792, will produce a reflected output beam 790 having an angle θ_o determined by Eq. 1 as adjusted for the blaze angle θ_g . This can provide another level of multiplexing bits in the code.

20 Referring to Fig. 16, instead of using an optical binary (0-1) code, an additional level of multiplexing may be provided by having the optical code use other numerical bases, if intensity levels of each bit are used to indicate code information. This could be achieved by having a corresponding magnitude (or strength) of the refractive index change (δn) for each grating pitch Λ . Four intensity ranges are shown
25 for each bit number or pitch Λ , providing for a Base-4 code (where each bit corresponds to 0,1,2, or 3). The lowest intensity level, corresponding to a 0, would exist when this pitch Λ is not present in the grating 12. The next intensity level 450 would occur when a first low level δn_1 exists in the grating that provides an output

signal within the intensity range corresponding to a 1. The next intensity level 452 would occur when a second higher level δn_2 exists in the grating 12 that provides an output signal within the intensity range corresponding to a 2. The next intensity level 452, would occur when a third higher level δn_3 exists in the grating 12 that provides an output signal within the intensity range corresponding to a 3.

Referring to Fig. 17, the input light 24 may be incident on the substrate 10 on an end face 600 of the substrate 10. In that case, the input light 24 will be incident on the grating 12 having a more significant component of the light (as compared to side illumination discussed hereinbefore) along the longitudinal grating axis 207 of the grating (along the grating vector k_B), as shown by a line 602. The light 602 reflects off the grating 12 as indicated by a line 604 and exits the substrate as output light 608. Accordingly, it should be understood by one skilled in the art that the diffraction equations discussed hereinbefore regarding output diffraction angle θ_o also apply in this case except that the reference axis would now be the grating axis 207. Thus, in this case, the input and output light angles θ_i, θ_o , would be measured from the grating axis 207 and length L_g of the grating 12 would become the thickness or depth D of the grating 12. As a result, a grating 12 that is 400 microns long, would result in the Bragg envelope 200 being narrow. It should be understood that because the values of n_1 and n_2 are close to the same value, the slight angle changes of the light between the regions 18,20 are not shown herein.

In the case where incident light 610 is incident along the same direction as the grating vector (K_b) 207, i.e., $\theta_i=0$ degrees, the incident light sees the whole length L_g of the grating 12 and the grating provides a reflected output light angle $\theta_o = 0$ degrees, and the Bragg envelope 612 becomes extremely narrow, as the narrowing effect discussed above reaches a limit. In that case, the relationship between a given pitch Λ in the grating 12 and the wavelength of reflection λ is governed by a known "Bragg grating" relation:

$$\lambda = 2 n_{eff} \Lambda \quad \text{Eq. 8}$$

where n_{eff} is the effective index of refraction of the substrate, λ is the input (and output wavelength) and Λ is the pitch. This relation, as is known, may be derived from Eq. 1 where $\theta_i = \theta_o = 90$ degrees.

In that case, the code information is readable only in the spectral wavelength of the reflected beam, similar to that discussed hereinbefore for wavelength based code reading. Accordingly, the input signal in this case may be a scanned wavelength source or a broadband wavelength source. In addition, as discussed hereinbefore for wavelength based code reading, the code information may be obtained in reflection from the reflected beam 614 or in transmission by the transmitted beam 616 that passes through the grating 12.

It should be understood that for shapes of the substrate 10 or element 8 other than a cylinder, the effect of various different shapes on the propagation of input light through the element 8, substrate 10, and/or grating 12, and the associated reflection angles, can be determined using known optical physics including Snell's Law, shown below:

$$n_{in} \sin \theta_{in} = n_{out} \sin \theta_{out} \quad \text{Eq. 9}$$

where n_{in} is the refractive index of the first (input) medium, and n_{out} is the refractive index of the second (output) medium, and θ_{in} and θ_{out} are measured from a line 620 normal to an incident surface 622.

Referring to Fig. 18, if the value of n_1 in the grating region 20 is greater than the value of n_2 in the non-grating region 18, the grating region 20 of the substrate 10 will act as a known optical waveguide for certain wavelengths. In that case, the grating region 20 acts as a "core" along which light is guided and the outer region 18 acts as a "cladding" which helps confine or guide the light. Also, such a waveguide will have a known "numerical aperture" (θ_{na}) that will allow light that is within the aperture θ_{na} to be directed or guided along the grating axis 207 and reflected axially off the grating 12 and returned and guided along the waveguide. In that case, the grating 12 will reflect light having the appropriate wavelengths equal to the pitches Λ present in the grating 12 back along the region 20 (or core) of the waveguide, and

pass the remaining wavelengths of light as the light 632. Thus, having the grating region 20 act as an optical waveguide for wavelengths reflected by the grating 12 allows incident light that is not aligned exactly with the grating axis 207 to be guided along and aligned with the grating 12 axis 207 for optimal grating reflection.

5 If an optical waveguide is used any standard waveguide may be used, e.g., a standard telecommunication single mode optical fiber (125 micron diameter or 80 micron diameter fiber with about a 8-10 micron diameter), or a larger diameter waveguide (greater than 0.5 mm diameter), such as is describe in U.S. Patent Application, Serial No. 09/455,868, filed December 6, 1999, entitled "Large Diameter
10 Waveguide, Grating". Further, any type of optical waveguide may be used for the optical substrate 10, such as, a multi-mode, birefringent, polarization maintaining, polarizing, multi-core, multi-cladding, or microsturctured optical waveguide, or a flat or planar waveguide (where the waveguide is rectangular shaped), or other waveguides.

15 Referring to Fig. 19, if the grating 12 extends across the entire dimension D of the substrate, the substrate 10 does not behave as a waveguide for the incident or reflected light and the incident light 24 will be diffracted (or reflected) as indicated by lines 642, and the codes detected as discussed hereinbefore for the end-incidence condition discussed hereinbefore with Fig. 45, and the remaining light 640 passes
20 straight through.

 Referring to Fig. 20, illustrations (a)-(c), in illustration (a), for the end illumination condition, if a blazed or angled grating is used, as discussed hereinbefore, the input light 24 is coupled out of the substrate 10 at a known angle as shown by a line 650. Referring to Fig. 20, illustration (b), alternatively, the input light
25 24 may be incident from the side and, if the grating 12 has the appropriate blaze angle, the reflected light will exit from the end face 652 as indicated by a line 654. Referring to Fig. 20, illustration (c), the grating 12 may have a plurality of different pitch angles 660,662, which reflect the input light 24 to different output angles as

indicated by lines 664, 666. This provides another level of multiplexing (spatially) additional codes, if desired.

5 The grating 12 may be impressed in the substrate 10 by any technique for writing, impressed, embedded, imprinted, or otherwise forming a diffraction grating in the volume of or on a surface of a substrate 10. Examples of some known techniques are described in US Patent No. 4,725,110 and 4,807,950, entitled "Method for Impressing Gratings Within Fiber Optics", to Glenn et al; and US Patent No. 5,388,173, entitled "Method and Apparatus for Forming Aperiodic Gratings in Optical Fibers", to Glenn, respectively, and US Patent 5,367,588, entitled "Method of
10 Fabricating Bragg Gratings Using a Silica Glass Phase Grating Mask and Mask Used by Same", to Hill, and US Patents 3,916,182, entitled "Periodic Dielectric Waveguide Filter", Dabby et al, and US Patent 3,891,302, entitled "Method of Filtering Modes in Optical Waveguides", to Dabby et al, which are all incorporated herein by reference to the extent necessary to understand the present invention.

15 Alternatively, instead of the grating 12 being impressed within the substrate material, the grating 12 may be partially or totally created by etching or otherwise altering the outer surface geometry of the substrate to create a corrugated or varying surface geometry of the substrate, such as is described in US Patent 3,891,302, entitled "Method of Filtering Modes in Optical Waveguides", to Dabby et al, which is
20 incorporated herein by reference to the extent necessary to understand the present invention, provided the resultant optical refractive profile for the desired code is created.

Further, alternatively, the grating 12 may be made by depositing dielectric layers onto the substrate, similar to the way a known thin film filter is created, so as to
25 create the desired resultant optical refractive profile for the desired code.

The substrate 10 (and/or the element 8) may have end-view cross-sectional shapes other than circular, such as square, rectangular, elliptical, clam-shell, D-shaped, or other shapes, and may have side-view sectional shapes other than rectangular, such as circular, square, elliptical, clam-shell, D-shaped, or other shapes.

Also, 3D geometries other than a cylinder may be used, such as a sphere, a cube, a pyramid or any other 3D shape. Alternatively, the substrate 10 may have a geometry that is a combination of one or more of the foregoing shapes.

5 The shape of the element 8 and the size of the incident beam may be made to minimize any end scatter off the end face(s) of the element 8, as is discussed herein and/or in the aforementioned patent application. Accordingly, to minimize such scatter, the incident beam 24 may be oval shaped where the narrow portion of the oval is smaller than the diameter D_1 , and the long portion of the oval is smaller than the length L of the element 8. Alternatively, the shape of the end faces may be rounded or
10 other shapes or may be coated with an antireflective coating. -

It should be understood that the size of any given dimension for the region 20 of the grating 12 may be less than any corresponding dimension of the substrate 10. For example, if the grating 12 has dimensions of length L_g , depth D_g , and width W_g , and the substrate 12 has different dimensions of length L , depth D , and width W , the
15 dimensions of the grating 12 may be less than that of the substrate 12. Thus, the grating 12, may be embedded within or part of a much larger substrate 12. Also, the element 8 may be embedded or formed in or on a larger object for identification of the object.

The dimensions, geometries, materials, and material properties of the substrate
20 10 are selected such that the desired optical and material properties are met for a given application. The resolution and range for the optical codes are scalable by controlling these parameters as discussed herein and/or in the aforementioned patent application.

Referring to Fig. 21, the substrate 10 may have an outer coating 799, such as a
25 polymer or other material that may be dissimilar to the material of the substrate 10, provided that the coating 799 on at least a portion of the substrate, allows sufficient light to pass through the substrate for adequate optical detection of the code. The coating 799 may be on any one or more sides of the substrate 10. Also, the coating

799 may be a material that causes the element 8 to float or sink in certain fluids (liquid and/or gas) solutions.

Also, the substrate 10 may be made of a material that is less dense than certain fluid (liquids and/or gas) solutions, thereby allowing the elements 8 to float or be
5 buoyant or partially buoyant. Also, the substrate may be made of a porous material, such as controlled pore glass (CPG) or other porous material, which may also reduce the density of the element 8 and may make the element 8 buoyant or partially-buoyant in certain fluids.

Referring to Fig. 22, the grating 12 is axially spatially invariant. As a result,
10 the substrate 10 with the grating 12 (shown as a long substrate 21) may be axially subdivided or cut into many separate smaller substrates 30-36 and each substrate 30-36 will contain the same code as the longer substrate 21 had before it was cut. The limit on the size of the smaller substrates 30-36 is based on design and performance factors discussed herein and/or in the aforementioned patent application.

Referring to Fig. 23, one purpose of the outer region 18 (or region without the grating 12) of the substrate 10 is to provide mechanical or structural support for the inner grating region 20. Accordingly, the entire substrate 10 may comprise the grating 12, if desired. Alternatively, the support portion may be completely or partially
15 beneath, above, or along one or more sides of the grating region 20, such as in a planar geometry, or a D-shaped geometry, or other geometries, as described herein and/or in the aforementioned patent application. The non-grating portion 18 of the substrate 10 may be used for other purposes as well, such as optical lensing effects or other effects (discussed herein or in the aforementioned patent application). Also, the
20 end faces of the substrate 10 need not be perpendicular to the sides or parallel to each other. However, for applications where the elements 8 are stacked end-to-end, the packing density may be optimized if the end faces are perpendicular to the sides.
25

Referring to Figs. 24, illustrations (a)-(c), two or more substrates 10,250, each having at least one grating therein, may be attached together to form the element 8,

e.g., by an adhesive, fusing or other attachment techniques. In that case, the gratings 12,252 may have the same or different codes.

Referring to Figs. 25, illustrations (a) and (b), the substrate 10 may have multiple regions 80,90 and one or more of these regions may have gratings in them. For example, there may be gratings 12,252 side-by-side (illustration (a)), or there may be gratings 82-88, spaced end-to-end (illustration (b)) in the substrate 10.

Referring to Fig. 26, the length L of the element 8 may be shorter than its diameter D, thus, having a geometry such as a plug, puck, wafer, disc or plate.

Referring to Fig. 27, to facilitate proper alignment of the grating axis with the angle θ_i of the input beam 24, the substrate 10 may have a plurality of the gratings 12 having the same codes written therein at numerous different angular or rotational (or azimuthal) positions of the substrate 10. In particular, two gratings 550, 552, having axial grating axes 551, 553, respectively may have a common central (or pivot or rotational) point where the two axes 551,553 intersect. The angle θ_i of the incident light 24 is aligned properly with the grating 550 and is not aligned with the grating 552, such that output light 555 is reflected off the grating 550 and light 557 passes through the grating 550 as discussed herein. If the element 8 is rotated as shown by the arrows 559, the angle θ_i of incident light 24 will become aligned properly with the grating 552 and not aligned with the grating 550 such that output light 555 is reflected off the grating 552 and light 557 passes through the grating 552. When multiple gratings are located in this rotational orientation, the bead may be rotated as indicated by a line 559 and there may be many angular positions that will provide correct (or optimal) incident input angles θ_i to the grating. While this example shows a circular cross-section, this technique may be used with any shape cross-section.

Referring to Fig. 28, illustrations (a), (b), (c), (d), and (e) the substrate 10 may have one or more holes located within the substrate 10. In illustration (a), holes 560 may be located at various points along all or a portion of the length of the substrate 10. The holes need not pass all the way through the substrate 10. Any number, size and spacing for the holes 560 may be used if desired. In illustration (b), holes 572

may be located very close together to form a honeycomb-like area of all or a portion of the cross-section. In illustration (c), one (or more) inner hole 566 may be located in the center of the substrate 10 or anywhere inside of where the grating region(s) 20 are located. The inner hole 566 may be coated with a reflective coating 573 to reflect light to facilitate reading of one or more of the gratings 12 and/or to reflect light diffracted off one or more of the gratings 12. The incident light 24 may reflect off the grating 12 in the region 20 and then reflect off the surface 573 to provide output light 577.

Alternatively, the incident light 24 may reflect off the surface 573, then reflect off the grating 12 and provide the output light 575. In that case the grating region 20 may run axially or circumferentially 571 around the substrate 10. In illustration (d), the holes 579 may be located circumferentially around the grating region 20 or transversely across the substrate 10. In illustration (e), the grating 12 may be located circumferentially around the outside of the substrate 10, and there may be holes 574 inside the substrate 10.

Referring to Fig. 29, illustrations (a), (b), and (c), the substrate 10 may have one or more protruding portions or teeth 570, 578, 580 extending radially and/or circumferentially from the substrate 10. Alternatively, the teeth 570, 578, 580 may have any other desired shape.

Referring to Fig. 30, illustrations (a), (b), (c) a D-shaped substrate, a flat-sided substrate and an eye-shaped (or clam-shell or teardrop shaped) substrate 10, respectively, are shown. Also, the grating region 20 may have end cross-sectional shapes other than circular and may have side cross-sectional shapes other than rectangular, such as any of the geometries described herein for the substrate 10. For example, the grating region 20 may have a oval cross-sectional shape as shown by dashed lines 581, which may be oriented in a desired direction, consistent with the teachings herein. Any other geometries for the substrate 10 or the grating region 20 may be used if desired, as described herein.

Referring to Fig. 31, at least a portion of a side of the substrate 10 may be coated with a reflective coating to allow incident light 510 to be reflected back to the same side from which the incident light came, as indicated by reflected light 512.

5 Referring to Fig. 32, illustrations (a) and (b), alternatively, the substrate 10 can be electrically and/or magnetically polarized, by a dopant or coating, which may be used to ease handling and/or alignment or orientation of the substrate 10 and/or the grating 12, or used for other purposes. Alternatively, the bead may be coated with conductive material, e.g., metal coating on the inside of a hollow substrate, or metallic
10 dopant inside the substrate. In these cases, such materials can cause the substrate 10 to align in an electric or magnetic field. Alternatively, the substrate can be doped with an element or compound that fluoresces or glows under appropriate illumination, e.g., a rare earth dopant, such as Erbium, or other rare earth dopant or fluorescent or luminescent molecule. In that case, such fluorescence or luminescence may aid in locating and/or aligning substrates.

15 Unless otherwise specifically stated herein, the term "microbead" is used herein as a label and does not restrict any embodiment or application of the present invention to certain dimensions, materials and/or geometries.

The dimensions and/or geometries for any of the embodiments described herein are merely for illustrative purposes and, as such, any other dimensions and/or
20 geometries may be used if desired, depending on the application, size, performance, manufacturing requirements, or other factors, in view of the teachings herein.

It should be understood that, unless stated otherwise herein, any of the features, characteristics, alternatives or modifications described regarding a particular embodiment herein may also be applied, used, or incorporated with any other
25 embodiment described herein. Also, the drawings herein are not drawn to scale.

Although the invention has been described and illustrated with respect to exemplary embodiments thereof, the foregoing and various other additions and omissions may be made therein and thereto without departing from the spirit and scope of the present invention.

Claims**What is claimed is:**

1. An optical identification element attached to a chemical, comprising:
5 an optical substrate;
at least a portion of said substrate having at least one diffraction grating
disposed therein, said grating having at least one refractive index pitch superimposed
at a common location;
the grating providing an output optical signal when illuminated by an incident
10 light signal;
said optical output signal being indicative of a code in said substrate; and
the chemical being attached to said substrate.
2. The apparatus of claim 1 wherein said substrate is made of a glass
15 material.
3. The apparatus of claim 1 wherein said code comprises a plurality of
bits.
4. The apparatus of claim 1 wherein the number of pitches is indicative of
the number of said bits in said code.
- 20 5. The apparatus of claim 1 wherein said substrate has a length that is less
than about 500 microns.
6. The apparatus of claim 1 wherein said substrate has a cylindrical
shape.
7. The apparatus of claim 1 wherein said grating is a blazed grating.
- 25 8. The apparatus of claim 1 wherein said code comprises a plurality of
bits, each bit having a plurality of states.
9. The apparatus of claim 1 wherein said substrate has a reflective coating
disposed thereon.

10. The apparatus of claim 1 wherein said substrate is has a magnetic or electric charge polarization.

11. The apparatus of claim 1 wherein said substrate has a grating region where said grating and a non-grating region where said grating is not located; and
5 wherein said substrate has a plurality of grating regions.

12. The apparatus of claim 1 wherein said substrate has geometry having holes therein.

13. The apparatus of claim 1 wherein said substrate is has a geometry having protruding sections.

10 14. The apparatus of claim 1 wherein at least a portion of said substrate is has an end cross sectional geometry selected from the group: circular, square, rectangular, elliptical, clam-shell, D-shaped, and polygon

15 15. The apparatus of claim 1 wherein at least a portion of said substrate is has a side view geometry selected from the group: circular, square, rectangular, elliptical, clam-shell, D-shaped, and polygon.

16. The apparatus of claim 1 wherein at least a portion of said substrate is has a 3-D shape selected from the group: sphere, a cube, a pyramid.

17. The apparatus of claim 1 wherein said code comprises at least a predetermined number of bits, said number being: 3, 5, 7, 9, 10, 12, 14, 16, 18, 20, 24,
20 28, 30, 40, 50, or 100.

18. A microparticle attached to a chemical comprising:
an optical substrate;
at least a portion of said substrate having at least one diffraction grating
disposed therein, said grating having at least one refractive index pitch superimposed
25 at a common location;
the grating providing an output optical signal when illuminated by an incident light signal;
said optical output signal being indicative of a code in said substrate; and
the chemical being attached to said substrate.

19. A method of synthesizing a chemical on an optical element,
comprising:

obtaining a optical element, comprising:

an optical substrate;

5 at least a portion of the substrate having at least one diffraction grating
disposed therein,

the grating having at least one refractive index pitch superimposed at a
common location;

10 the grating providing an output optical signal when illuminated by an
incident light signal; and

the optical output signal being indicative of a code; and
attaching a chemical to the element.

20. The apparatus of claim 1 wherein said element is made of a glass material.

15





Fig. 3




Fig. 4




Fig. 5







Fig. 8


89 17 bits turned on



Bits: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

(a)

89 7 bits turned on



Bits: 1 0 1 1 0 0 1 0 0 0 1 0 0 1 0 0 1

(b)

89 9 bits turned on



Bits: 1 1 0 0 0 1 0 1 0 1 0 1 0 0 1 1 1

(c)

Fig. 9






Fig. 9
(d)

Index modulation caused by superposition of 3 gratings where the pitch between each grating varies by 3%.




Fig. 10








Fig- 11














Fig. 20










Fig. 28




Fig. 29





Fig. 30







Fig. 32



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/28887

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06T5/00 //G02B6/16, G02B6/34, G01N33/52

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G02B B01J G01N G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 096 496 A (FRANKEL ROBERT D) 1 August 2000 (2000-08-01) cited in the application	1-4,7-9, 11-19
Y	column 5, line 15 -column 5, line 45 column 11, line 4 -column 11, line 12 column 11, line 27 -column 11, line 51 column 13, line 36 -column 13, line 53 column 13, line 61 -column 14, line 6 column 17, line 18 -column 17, line 24 column 21, line 1 -column 26, line 67 column 27, line 53 -column 28, line 47 column 30, line 10 -column 31, line 15 column 31, line 56 -column 33, line 64 figures 13-16 --- -/--	5,6

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

° Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

29 January 2004

Date of mailing of the international search report

05/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Koch, A

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 03/28887

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6 340 588 B1 (NOVA MICHAEL P ET AL) 22 January 2002 (2002-01-22) column 1, line 40 -column 1, line 43 column 5, line 54 -column 7, line 12 column 8, line 4 -column 8, line 12 column 9, line 53 -column 10, line 29 column 10, line 62 -column 10, line 66 column 35, line 44 -column 36, line 2 column 44, line 34 -column 45, line 5 column 45, line 48 -column 45, line 61 ---	5
Y	WO 01 58583 A (ONTOGEN CORP) 16 August 2001 (2001-08-16) page 8, line 1 -page 8, line 5 page 9, line 13 -page 9, line 15 page 10, line 11 -page 10, line 14 ---	6
X	US 5 671 308 A (YAMASHITA KATSUYA ET AL) 23 September 1997 (1997-09-23) column 6, line 24 -column 7, line 11 column 8, line 34 -column 8, line 60 column 9, line 1 -column 9, line 16 column 12, line 6 -column 12, line 36 figures 1-17 ---	1-4, 8, 14, 19
X	GB 2 372 100 A (MARCONI CASWELL LTD ;BOOKHAM TECHNOLOGY PLC (GB); MARCONI OPTICAL) 14 August 2002 (2002-08-14) page 2, line 3 -page 3, line 23 page 4, line 19 -page 4, line 22 page 7, line 1 -page 8, line 2 ---	1, 3, 6, 14, 17
P, X	WO 03 061983 A (STEENBLIK RICHARD A ;HURT MARK J (US); KNOTTS MICHAEL E (US); NANO) 31 July 2003 (2003-07-31) page 1, paragraph 1 page 5, line 24 -page 7, line 16 page 8, line 20 -page 9, line 28 page 11, line 4 -page 11, line 7 page 13, line 1 -page 14, line 9 page 15, line 1 -page 15, line 14 page 16, line 10 -page 17, line 19 figures 1-29 ---	1, 9, 12, 13
X	EP 1 219 979 A (NIPPON MITSUBISHI OIL CORP) 3 July 2002 (2002-07-03) page 2, line 11 -page 2, line 46 page 3, line 25 -page 3, line 41 page 3, line 57 -page 4, line 3 page 5, line 50 -page 5, line 52 page 7, line 3 -page 7, line 13 page 7, line 48 -page 7, line 51 -----	1, 2, 11-13

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/28887

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6096496	A	01-08-2000	US 6506342 B1	14-01-2003
US 6340588	B1	22-01-2002	US 5961923 A	05-10-1999
			US 6017496 A	25-01-2000
			US 6284459 B1	04-09-2001
			US 6319668 B1	20-11-2001
			US 6100026 A	08-08-2000
			US 6025129 A	15-02-2000
			US 5874214 A	23-02-1999
			US 6352854 B1	05-03-2002
			US 6416714 B1	09-07-2002
			US 5751629 A	12-05-1998
			US 5925562 A	20-07-1999
			US 6331273 B1	18-12-2001
			US 5741462 A	21-04-1998
			AU 3577997 A	14-01-1998
			AU 7257396 A	28-04-1997
			EP 0853497 A2	22-07-1998
			WO 9712680 A2	10-04-1997
			WO 9749653 A2	31-12-1997
			US 6329139 B1	11-12-2001
			AT 254965 T	15-12-2003
			AU 707444 B2	08-07-1999
			AU 5918596 A	29-11-1996
			DE 69630881 D1	08-01-2004
			EP 0822861 A1	11-02-1998
			JP 11511238 T	28-09-1999
			CA 2216645 A1	21-11-1996
			CN 1181720 A	13-05-1998
			WO 9636436 A1	21-11-1996
			US 6372428 B1	16-04-2002
WO 0158583	A	16-08-2001	US 6528324 B1	04-03-2003
			AU 3673801 A	20-08-2001
			CA 2366494 A1	16-08-2001
			EP 1173276 A1	23-01-2002
			JP 2003522016 T	22-07-2003
			WO 0158583 A1	16-08-2001
			US 2003134432 A1	17-07-2003
US 5671308	A	23-09-1997	JP 5307118 A	19-11-1993
			JP 3078103 B2	21-08-2000
			JP 5307119 A	19-11-1993
			JP 3078104 B2	21-08-2000
			JP 5307120 A	19-11-1993
			JP 3129831 B2	31-01-2001
			JP 5307121 A	19-11-1993
			JP 3078105 B2	21-08-2000
			JP 5307122 A	19-11-1993
			JP 5313020 A	26-11-1993
			JP 3078106 B2	21-08-2000
			JP 5313021 A	26-11-1993
			AU 4271393 A	29-11-1993
			CA 2112692 A1	02-11-1993
			CN 1082717 A , B	23-02-1994
			CN 1249576 A	05-04-2000
			DE 69321548 D1	19-11-1998
			DE 69321548 T2	15-04-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/28887

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5671308	A		DE 69333369 D1	29-01-2004
			EP 0592690 A1	20-04-1994
			EP 0851248 A2	01-07-1998
			WO 9322647 A1	11-11-1993
			KR 9704993 B1	10-04-1997
			KR 148255 B1	17-08-1998
			NO 934917 A	24-02-1994
			US 5506674 A	09-04-1996
GB 2372100	A	14-08-2002	WO 02065181 A2	22-08-2002
WO 03061983	A	31-07-2003	WO 03062900 A1	31-07-2003
			WO 03061983 A1	31-07-2003
			US 2003179364 A1	25-09-2003
			US 2003232179 A1	18-12-2003
EP 1219979	A	03-07-2002	JP 2001091715 A	06-04-2001
			EP 1219979 A1	03-07-2002
			US 2002101560 A1	01-08-2002
			CN 1376271 T	23-10-2002
			WO 0123917 A1	05-04-2001